

Design and Implementation of Smart-H Pot: A Custom Intrusion Detection System

Dr. G. Vasavi¹, G. T. S. Satyanarayana², B. Vivek Sai³, B. Chaitanya S. S. Phani⁴ ¹Assistant professor, Dept. of Cybersecurity, Malla Reddy University., Hyderabad, Telangana, India. ^{2,3,4}UG Scholar, Dept. of Cybersecurity, Malla Reddy University., Hyderabad, Telangana, India. **Emails:** vasavi.gotte@gmail.com¹, satya2a5i@gmail.com², viveksai8840@gmail.com³, chaitanyachowdary5722@gmail.com⁴

Abstract

In the digital world with all new cyber threats evolving constantly, protecting digital world from unauthorized access with new threats is more important than ever. Traditional Intrusion Detection Systems (IDS) often fail in capturing real-world attacker behavior due to this constant evolving. To fill the gap of evolving, we are introducing Smart-HPot a lightweighted, custom-built IDS that basically uses a honeypot approach to detect and monitor malicious activities in real time. The system provides the services such as SSH and HTTP within a controlled virtual environment, tempting attackers to attack the honeypot and logging their actions without compromising actual infrastructure. Developed using Python's built-in modules like socket and logging, Smart-HPot records interaction data and sends it to Admin Website which is a user-friendly web dashboard powered by Flask, enables admin with real-time threat visualization and tracking. Unlike traditional IDS tools, Smart-HPot will be easy to deploy, resource-efficient, and can be adaptable to different network environments. This design used in it makes it suitable for both small scale organizations and academic research cybersecurity operations. By offering a clear view of attacker's behavior and patterns, Smart-HPot stands as a cost-effective and proactive security measure. The project highlights the importance of deception technology and sets the stage for future enhancements.

Keywords: Attacks Alerts System; Attacks Monitoring System; Deception Technology; Honeypot Security; Logging Attacks.

1. Introduction

Smart-HPot is utilizing a combined approach of implementing a honeypot and Intrusion Detection System by hosted in a VMware environment and honeypot system come within a deception technology, capitalizing between these two security measures to enhance the threat detection and response capabilities by creating Admin window and following up the alerts. Smart-HPot provides vulnerable SSH and HTTP services which are fake and used only to trap attackers. Once engaged, the system accurately tracks malicious behavior of the intruder/attacker while triggering real-time alerts and details to admin window which is under the control of the Cyber analysis team. This multi-protocol capability transforms the honeypot into an effective sinkhole for cyber threat analysis. The Smart-HPot is considered to be early form the deception technology,

it's a well-structured cybersecurity strategy that functions as a decoy system to trap the attacker/intruder by simulating vulnerable system and faking service. The main motive of this Smart-HPot's system forge or counterfeit attackers by fake services. These traps are designed to misguiding malicious actors, allowing for the logging attacks and analysis of their behaviors without exposing real world organization systems to harm[8]. By presenting it which appears to be a vulnerable environment, generally honeypots appear to be a vulnerable environment and gather authentic threat intelligence and uncover attack vectors that might otherwise go undetected. This deception-based defense method marks a shift from reactive security measures to a more proactive and insightful approach. Traditional Intrusion Detection Systems



mainly rely on heavily known pattern recognitions, often through signature-based detection. As such systems may fall short while facing a zero-day or evolving threats[1][2]. Honeypots, with their ability to record live attacks, offer a powerful supplement by enabling organizations to understand novel intrusion attempts in real time. When integrated, honeypots and IDS form a sophisticate threat-detection ecosystem which not only detects but also learns from each attack, improving overall security posture[3][4]. This is what differentiates Smart-HPot which is its dual-layered architecture, comprising both deception and detection, thus maximizing security intelligence. The project not only facilitates cybersecurity awareness and ethical hacking research but, can also supports proactive defense planning in Organizations.

2. Literature Survey

The Honeypots are used Cyber Sector especially in defense and the analysis of cyber cyber attack/intrusions has been extensively explored in academic research. The Kippo Honeypot (2014) showcased its capability to effectively monitor SSH brute-force attacks[9]. while tools such as Cowrie and Dionaea expanded their variety of attack vectors supported[10]. The initial investigations, such as those conducted by Spitzner (2003), are defined honeypots as security traps[8]. Subsequently research concentrated on the improvement of the deception strategies which are considered to be the basis of trap and decoys systems. However, the majority of the current honeypots systems either depend on the cloud infrastructure or engineered to oversee specific services like SSH[14]. Collectively, datasets such as CICIDS 2017[12] and UNSW-NB15[13] have offered significant insights real-world into attacker/intruder behaviors, contributing to the development of machine learning-based security solutions where the model is trained with previous attacks. Unlike traditional systems, Smart-HPot presents actionable intelligence for researchers and cybersecurity professionals functioning within both Indian and international network environments. Smart-HPot enhances this body of knowledge by providing a lightweight program, self-sustaining honeypot that integrates multi-protocol deception and

real-time alerting functionalities[5].

3. System Analysis

3.1.Existing System

Traditionally, Intrusion Detection System have primarily used either two methods. They are anomaly-based signature-based or detection methods, the signature-based system which directly focusing on known attack patterns and anomalybased system mainly detecting deviations from normal behavior. Tools such as Snort and Suricata are the specifically designed to identify recognized attack patterns only. however, but this design can't withstand a zero-day vulnerabilities[6]. Although this machine learning-based IDS can enhance detection capabilities, they frequently result in a high rate of false positives as well[7], which necessitates the use of manual monitoring. Honeypots such as Dionaea and Cowrie offer a certain level of intrusion monitoring; however, they possess limited protocol support and are contingent upon specific network configurations. This limitation make them unsuitable for private organizations[11] and government entities, where data privacy and control are of utmost importance. These challenges underscore the necessity for a localized, deception-based sinkhole that can function independently, delivering insights into attacker behavior without depending on external resources.

3.2.Proposed System

Smart-HPot is a specifically designed honeypotbased intrusion detection system that offers a lightweight system, real-time threat detection and alerting system, and adaptive security solution for organizations. In contrast to the traditional signaturebased intrusion detection systems, which can frequently encounter difficulties in identifying a new and emerging threats, Smart-HPot serves as an interactive lure, tempting attackers into a controlled VMware environment where their actions can be monitored and logged. This system functions within a VMware environment and accommodates a variety of network protocols, such as SSH and HTTP, which are commonly targeted by cybercriminals. It meticulously records every interaction, capturing essential information such as IP addresses, attempted exploits, and commands executed by attackers. The



data collected helping cybersecurity professionals to identify the intruders/hacking patterns and improve there defensive strategies. A notable feature of Smart-HPot is its capacity to mislead attackers with realistic system responses, creating the illusion that they are interacting with a genuine server. Thus, the developed honeypot system can deliver the real-time alerts and logs of the attacker pattern/behavior to Admin window, the administration of organization can only access the Admin window and analysis the behavior of the attacker/intruder via the logs generated, then the analysis is deported to incident response teams. This project is designed particularly advantageous for organizations, and research institutions, as it for the strengthening cybersecurity measures. Bv implementing Smart-HPot, organizations can proactively protect against intruder threats, reduce potential via breaches, and enhance security awareness among IT teams of organizations.

3.3.Advantages

- **Multi-Protocol System:** Generating fake SSH and HTTP services attacks for in-depth examination.
- **Deception Technology:** decoys, traps, make system appear vulnerable and Offer fake services to mislead attackers.
- **Real-Time Alerts System:** Sends immediate alerts and overview of intrusion to Administrator/Incident Response Team via Admin window.
- **Cloud Independence:** Functions in isolated network environments like VMware.
- **Customizability:** Can be customized to meet various security research needs.

4. Methodology

The Smart-HPot is an advanced deception-based intrusion detection system specifically designed to capture logs of attacker behavior/ pattern and analyze unauthorized access attempts within a secure virtual environment (VMware). Now the methodology comprises multi-portal, ensuring effective detection, logging, and response to attacks.

• Attack Initiation – The process begins when a threat acter intrude(unauthorized) to gain access by sending SSH or HTTP[9] requests to the Smart-HPot.

- **Honeypot Interaction** The Smart-HPot acts as a decoy, it receives the requests to access and capturing incoming malicious requests and analyzing their features[10].
- Log Processing & Categorization –Upon receiving a request, it is categorized into one of two log types:
- SSH Log Tutor processes unauthorized login attempts targeting SSH.
- HTTP Log Tutor documents unauthorized web-based interaction. (Figure 1)





- **Data Transmission** –The processed logs are sent via an API to the Smart-HPot Admin Backend for further analysis[12].
- Storage & Monitoring –The logs are stored in a MongoDB database for future review/analysis[13]. The Smart-HPot Admin Frontend provides a user-friendly interface for displaying these logs which can help Incident Response Team for quick response.
- **Real-Time Analysis & Dashboard** –A realtime dashboard illustrates ongoing threats and delivers analytical insights for cybersecurity professionals[15] and also provide an overview as well.
- Alert Notification System –If an attacker attempt an attack, the log processing & Categorization will take control and generate logs, the system activates alerts, allowing security teams to respond swiftly.

This systematic approach ensures proactive threat detection which is required, positioning Smart-HPot as an indispensable resource for cybersecurity monitoring and analysis.

5. Results

Smart-HPot's has Fake SSH and HTTP modules function as honeypot trap system, imitating authentic services to trap in potential intruder/threat actors. They capture and log illicit activities, providing valuable data for cybersecurity assessments and intrusion detection efforts. (Figure 2)

- AC		Your Battery is discharging
C)	EXPLORER	🗠 🔮 config.py 🔹 soh_service.py 🔮 main.py
	✓ SMART-HPOT	
2		1 from co) password As ats .* No results 1 + = ×
		2 From CO
29		a trom contig import musi, pont
°		
~		0 if name " main ":
a~		
140		
EB.		9 listener_thread = threading.Thread(target=start_li
	config.py	10 ssh_thread = threading.thread(target=start_ssh_ser
		10 Distance thread start()
		13 ssh thread, start()
		15 except Keyboardinterrupt:
		property county property property in Distance in the Distance of the
		SSU Login Attempt - Username: admin . Bassword: chocolate
		SSH Login Attempt - Username: admin, Password: password1
		Connection from ('127.0.0.1', 33078)
		55H Login Attempt - Username: admin, Password: 12345
		SSH Login Attempt - Username: admin, Password: anthony
		SSH Login Attempt - Username: admin, Password: friends
		SSH Login Attempt - Username: admin, Password: butterfly
(8)		SSH Login Attempt - Username: admin, Password: purple
		SSH Login Attempt - Username: admin, Password: jordan
£63	> OUTLINE	55H Login Attempt - Username: admin, Password: liverpool
- 44	> TIMELINE	
- M - 1	80 <u>4</u> 0 %0	in 16, Col 26 Spaces: 4 I/TF-8 I/F Python

Figure 2 Smart-HPot Code Detecting Password Attack

The Admin Window is the second module of this project where the recorded data logs of attacker /intruder is stored in the mongoDB database of honeypot. this is transmitted to Admin Window. The Admin window contain dashboard which can display all alerts in real time, and also include multiple functions as well (Figure 3)

Dashboard	SSH Logs	HTTP Logsreport
Sm	art-H	Pot Dashboard
Ove	erview	Alerts
Suspici	ous Activity	
🔺 S	iuspicious act	vity from IP: 127.0.0.1
s s	uspicious act	vity from IP: 192.168.1.40

Figure 3 Admin Window Displaying Alerts

A summary of attack statistics, including the overall count of SSH and HTTP attacks along with the distinct attacker IPs, is presented in the Admin Window. This integrated dashboard enables administrators to track threats, analyze trends, and enhance security measures effectively. (Figure 4)

e sur na anna liedar x (X G gegetprine.	ante A M But Act				0	- A.
→ O (O localrest300)					Gź	÷ 0	-
🗑 LinurCommandiorge. 🧳 GraveSur	rhal (14he 🧥 Harre (Linus Journe) 🕌 40 Ease Linux Com	 Q ToyHaddire Desite . 6 ChatSPT 					
10:43:20 PM	10-43-20 PM 10-43:19 PM	10/43/19 PM	10:43:18 PM	10:42:17 PM	9:32:59 PM		3
P	Nethod	Usemane		Timestamp			
127.0.0.1	NA	admin		10:23:17 PM			
127.0.0.1	NA	admin		10.23.17 PM			
127.0.0.1	NA	admin		10.23.17 PM			
127.0.0.1	NA	admin		10:23:17 PM			
127.0.0.1	NA	admin		10:23:16 PM			
127.0.0.1	NA	admin		10.23.16 PM			
127.0.0.1	NA	acmin		10:23:16 PM			
127.0.0.1	NA	admin		10.23.16 PM			
127.0.0.1	NA	admin		10.23.16 PM			
127.0.0.1	NA	admin		10:22:57 PM			
127.0.0.1	NA	acmin		10.22.57 PM			
127.0.0.1	NA	admin		10.22.57 PM			

Figure 4 Displaying Attacker Details

A summary of attack, including SSH and HTTP attacks along with the distinct attacker IDs, is presented in the Admin Window. This integrated dashboard enables administrators to track threats, analyze trends, and enhance security protocols effectively. (Figure 5)



Overview Allerts			
Social SSM Accompto 256	Total HTTP Requests 14	Unique IPs 3	
1			
875-			
85			
8.25-			

Figure 5 Display Analysis

The Admin Window will display all SSH attack logs, which display attacker IP addresses, attempted usernames, passwords, and timestamps. Administrators can review specific logs, can investigate intrusion attempts, and analyze trends as well. Additionally, all logs can be downloaded in CSV/JSON formats for further analysis also. (Figure 6)



Figure 6 Displays all SSH Logs Details

The Admin Window displays all HTTP attack logs, which displays attacker IP addresses, request headers, dates, and timestamps. Administrators can review specific logs, monitor suspicious activities, and analyze patterns of attackers. It strengthens cybersecurity measures, all logs are available for download in CSV format for further forensic investigation. (Figure 7)



Administrators have capability to generate attack report by specifying start and end timestamps in the Analyze section of the Admin Window. This function allows the extraction of logs for analysis within a designated time period. This provided data consist of attackers IP addresses, Time stamps, Usernames and Passwords/ headers according to report (Figure 8)

nerate Report			
22/2825 🗖 03/24/28	25 🔲 Gereente		
port Summary			
atal Logic 774 stal SSH Attempts: 767 atal HTTP Requests: 7			
Inique IPs: 4 Aost Common Attack: 55H Bru	te Force		
nique IPs: 4 fost Common Attack: SSH Brut gr	te Force Type	Data	linestarp
nigoe IPs; 4 ost Cennon Attack; 55H Bru IP 2.80.1	te Force SSH	Data User admin, Pass 12345	Timestanp 3/23/02/5, 211-01 PM
Integrate (Fig. 4 Host Common Attack: 55H Brut (Fig. 2) 27 D.0.1	S2H 22H 22H	Dete Lizer, admin, Pass. 1235 Lizer, admin, Pass. 12355789	Timestonp 3/23/2023, 211541 PM 3/23/2025, 211541 PM
nigue (Pr. 4 Irost Common Attack: 35H Brut 97 82,00,1 17,00,1	re Force 55H 55H	Deta User admin, Parz 1245 User admin, Parz 12455789 User admin, Parz 12455789	Limestang 3/23/005, 2114F FM 3/22/005, 2114F FM 3/23/005, 2114F FM
Integra (Pro. 4 Root Common Attacks SSH Brut 27.00.1 27.00.1 27.00.1 27.00.1	te Force 55H 55H 55H 55H	Data User solmi, Parc 123-0 User solmi, Parc 123-05789 User solmi, Parc Europeu User solmi, Parc Europeu	TimeStory 3/23/2025, 21141 PM 3/23/2025, 21141 PM 3/23/2025, 21141 PM 3/23/2025, 21141 PM
Integra (Pr. 4 Rost Common Attacks SSH Brut 27 Do.1 27 Do.1 27 Do.1 27 Do.1 27 Do.1 27 Do.1	19 Force 594 594 594 594 594 594	Dete User solms, Prez 1216 User adms, Prez 12161789 User admin, Prez Janopet User admin, frez Janopet	10000000000000000000000000000000000000

Figure 8 Analyze and Generate Report

The reports provided in the Analyze section provide a summary of attack logs categorized by specific timestamps. The reports are available in both CSV and JSON formats for further analysis. They have details of SSH and HTTP attempts, unique IP addresses, and prevalent attack types. (Figure 9)

	http		
2.168.1.40	http	N/A	3/13/2025, 10:43:19 PM
2.168.1.40	http	N/A	3/13/2025, 10:43:20 PM
2.168.1.40	http	N/A	3/13/2025, 10:43:20 PM

Figure 9 Download Generated Report in CSV & JSON Files

The downloaded CSV file contain attackers data, like IP addresses, types of attempts(ssh/http), timestamps, and request details according to attack. This organized format allows administrators to analyze the information with ease, facilitating the of intrusion trends and the enhancement of security measures. (Figure 10) During the process of testing, Smart-HPot proficiently detected and documented SSH bruteforce attacks, HTTP directory traversal attempts, and suspicious Telnet activities[11]. The deception-based responses successfully misled the attackers, whilst real-time alert system offered prompt the notifications. The logs generated from the sinkhole disclosed complex patterns of malicious interactions, thereby illustrating its effectiveness as a network defense mechanism[13].



F	ile Ho	me Ins	ert Page L	nyout Fo	rmulas (lata Ren	ew View	Help	V Tell me	what you wan	to do	
1	Xor		Calibri		- K K		- 46	th Wap Te		General		1K
Per	te d'icen		BIU		0 - A -	* * *	(TE 22)	Herge &	Center -	5-16-1	51.25	
	Clipboard	1		Font			Alignm	ent		Number		
A1		+ =	x	fr IP								
1	A	в	c	D	E	F	G	н	1.1	J	к	L
1	IP	Type	Data	Timestan	np							
2	192.168.1	http	N/A		# 9:32:59	PM						
3	192.168.1	http	N/A	-	# 10:42:1	7 PM						
4	192.168.1	http	N/A	-	# 10:43:10	B PM						
5	192.168.1	http	N/A	-	# 10:43:19	9 PM						
6	192.168.1	http	N/A		# 10:43:1	P PM						
7	192.168.1	http	N/A		# 10:43:20	D PM						
8	192.168.1	http	N/A	-	# 10:43:20	D PM						
9												
10												
11												
12												
13												
14												

Figure 10 Downloaded Details of Attackers

Conclusion

Smart-HPot is an extremely lightweight, deceptionbased intrusion detection honeypot that effectively monitors cyber threats in real-time. By visualizing vulnerabilities to administrator, it produces detailed attacker logs, to defend organization against the threat actors and also enabling cybersecurity researchers to examine emerging attack patterns as well. Unlike cloud-based honeypots, it ensures data privacy and total control over network security. With its capability to support various protocols, deceptive strategies, and real-time alerts, Smart-HPot acts as a significant asset for ethical hacking research and cybersecurity awareness.

Future Scope

Smart-HPot can be further enhanced by integrating AI-based detection which can add a weighted advantage to the existing project, and can enables automated troubleshooting as well. Additionally, its functionalities will strengthen ICS/SCADA security system, rendering it significant for the safeguarding of both artificial and critical infrastructure[10]. Therefore, the integration of multiple honeypots can improve collaborative threat intelligence across diverse networks. Predictive analytics driven by machine learning can aid in real-time threat prevention. In India, where awareness of cybersecurity is increasing, Smart HPot can serve as essential research tool for cybersecurity an professionals, ethical hackers, and government entities, facilitating proactive defense against cyber threats[13].

References

 [1]. Hoque, M. S., Mukit, M. A., & Bikas, M. A.
 N. (2012). An implementation of intrusion detection system using genetic algorithm. Shahjalal University of Science and Technology, Bangladesh.

- [2]. Kakad, A. R., Kamble, S. G., Bhuvad, S. S., & Malavade, V. N. (2014). Study and Comparison of Virus Detection Techniques. International Journal of Advanced Research in Computer Science and Software Engineering.
- [3]. Khattab, S., Melhem, R., Mossé, D., & Znati, T. (2004). Honeypot back-propagation for mitigating spoofing distributed Denial-of-Service attacks. University of Pittsburgh, USA.
- [4]. Kuwatly, I., Sraj, M., & Al Masri, Z. (2004).A Dynamic Honeypot Design for Intrusion Detection. American University of Beirut.
- [5]. Almotairi, S., Clark, A., Mohay, G., & Zimmermann, J. (2007). A Technique for Detecting New Attacks in Low-Interaction Honeypot Traffic. Queensland University of Technology, Australia.
- [6]. Gupta, B. B., Joshi, R. C., & Misra, M. (2012). Distributed Denial of Service Prevention Techniques. IEEE.
- [7]. Kambow, N., & Passi, L. K. (2014). Honeypots: The Need of Network Security. International Journal of Computer Science and Information Technologies, 5(5), 6098-6101.
- [8]. Spitzner, L. (2003). Honeypots: Tracking Hackers. Addison-Wesley Professional.
- [9]. Kippo Honeypot. (2014). SSH Brute Force Detection and Logging.
- [10]. Cowrie Project. (2009). A Medium-Interaction SSH and Telnet Honeypot.
- [11]. Dionaea Honeypot. (2017). A Low-Interaction Malware Capture Honeypot.
- [12]. CICIDS 2017 Dataset. Canadian Institute for Cybersecurity Intrusion Detection System Dataset. University of New Brunswick.
- [13]. UNSW-NB15 Dataset. A Hybrid Intrusion Detection Dataset for Cybersecurity Research. University of New South Wales.
- [14]. Singh, A., & Sharma, P. Machine Learning for Intrusion Detection Using Honeypots: A Survey. International Journal of Cyber Security.